



## Studio 100

Design	5 driver, 3-way floorstanding
Crossover	3rd-order electro-acoustic at 2.0 kHz, 3rd-order electro-acoustic at 300 Hz (bass drivers)
High-Frequency Driver	25-mm (1 in) G-PAL™ dome, die-cast heatsink chassis, ferro-fluid cooled, IMS / SHOCK-MOUNT™
Bass / Midrange Driver(s)	-
Midrange Driver(s)	38-mm (1-1/2 in) voice coil, ferro-fluid cooled, AVS™ die-cast heatsink chassis, IMS / SHOCK-MOUNT™, 178-mm (7 in) S-PAL™ cone
Bass Driver	AVS™ die-cast heatsink chassis, Three 178-mm (7 in) mineral-filled polypropylene cones, IMS / SHOCK-MOUNT™, 38-mm (1-1/2 in) voice coils
Low Frequency Extension	28 Hz (DIN)
Frequency Response:	
On-Axis	±2 dB from 44 Hz - 22 kHz
30° Off-Axis	±2 dB from 44 Hz - 20 kHz
Sensitivity - Room / Anechoic	91 / 88 dB
Suitable Amplifier Power Range	15 - 350 watts
Maximum Input Power	210 watts
Internal Volume	67 L / 2.4 cu fut
Impedance	Compatible with 8 ohms
Weight	73.5 kg / 162 lb per pair
Height, Width, Depth	113 cm x 21 cm x 43.2 cm
(Height includes spikes or outrigger feet)	44-1/2 in x 8-1/4 in x 17-1/64 in
Finishes	Rosenut, Black Ash, Cherry